

## Kkalpana Industries (India) Limited

GRADE	KILAMIDE PA6 615G
FEATURE	PA6 15 % GF INJ MOL GRADE APPLICATION
PRESENTATION	NATURAL/BLACK

## **TENTATIVE TECHNICAL DATA SHEET**

PROPERTIES	ASTM TEST METHOD	TEST CONDITION	UNIT	KILAMIDE PA6 615 G COLOR XXXX
PHYSICAL PROPERTIES at 23 °C				
Specific Gravity*	D-792	-	-	1.22±0.01
THERMAL PROPERTIES Heat Deflection Temperature 12.7mm×6.4mm×127mm Bar	D-648	- 18.56 Kg/cm²	°C	190
FLAMMABILITY	UL-94			HB
MECHANICAL PROPERTIES				
Notched izod impact strength	D-256	3.2mm At 23°c	Kgfcm/cm	4±01
Tensile Strength at yield	D-638	50 mm/min	Kg/cm²	750±50
Flexural Strength	D-790	5 mm/min	Kg/cm²	1350±100
Flexural Modulus*	D-790	5 mm/min	Kg/cm²	50000±1000
	ĺ			

To be measured as & when necessary

It is necessary to pre-dry material at 85°C for 2 to 3 hours prior to processing.

## **DISCLAIMER:**

The above Technical Data Sheet presents information and data, true and accurate to the best of our

No warranty express or implied can be made regarding performance or otherwise.

(As this is computer generated, no signature is required)