

## Kkalpana Industries (India) Limited

GRADE	KKALPALON PC XX
FEATURE	PC GEN PURPOSE INJ. MOL GRADE APPLICATION
PRESENTATION	NATURAL / PRECOLORED / BLACK

## TECHNICAL DATA SHEET

				KKALPALON PCXX
PROPERTIES	ASTM TEST	TEST CONDITION	UNIT	COLOR XXXX
T KOT EKTIEG	METHOD	CONDITION		(VALUE)
PHYSICAL PROPERTIES at 23 °C Melt Flow Rate	D-1238	300°C/1.2 kg	gm/10 min	12±1
Specific Gravity*	D-792	-	-	1.2±0.02
THERMAL PROPERTIES				
Vicat Softening Temperature	D-1525	-	°C	133 ± 2
FLAMMABILITY	UL-94			НВ
MECHANICAL PROPERTIES				
Notched Izod impact strength	D-256	3.2mm At 23°c	Kgfcm/cm	67 ± 5
Tensile Strength at yield	D-638	50 mm/min	Kg/cm²	700 ± 100
Flexural strength	D-790	5 mm/min	Kg/cm²	850 ± 100
Flexural Modulus*	D-790	5 mm/min	Kg/cm²	24000 ± 1000

To be measured as & when necessary

It is necessary to pre-dry material at 85°C for 2 to 3 hours prior to processing.

## **DISCLAIMER:**

The above Technical Data Sheet presents information and data, true and accurate to the best of our knowledge. No warranty express or implied can be made regarding performance or otherwise.

(As this is computer generated, no signature is required)