PVC FOOT WEAR COMPOUND

AIR BLOWN GRADE: KI-55

DESCRIPTION:

The PVC Footwear compound is made by high quality pvc resin Suitable for injection air blown application. This is suitably compounded with additives & stabilizer to achieve excellent properties alongwith good processability and surface gloss.

APPLICATIONS:

- Safety Shoes1
- School Shoes, Leisure shoes.1
- Soles and Midsoles1
- Boots etc.1

SPECIAL CHARACTERISTICS:

- Properly dispersed Foaming agent in the compound ensure uniform micro-porous foam structurel
- Low volatile generation during processing.1
- Excellent surface smoothness.
- Better mechanical properties and dimensional stability.
- Excellent physical and thermal property.
- Optimum Balance of properties and processability.

TECHNICAL CHARACTERISTICS:

PROPERTY	TEST METHOD	GRADE NAME - KI-55
Specific gravity before blowing	ASTM-D792	1.17 <u>+</u> 0.02
Hardness, shore ⁰ A	ASTM-D2240	56 <u>+</u> 2
Thermal Stability@ 200°C minutes	IS 10810(PART-60)1988	25
Tensile Strength, Mpa	IS 10810 (PART-7) 1984	>8.0
Elongation at Break %	IS 10810 (PART-7) 1984	>250
Volatile Loss@130°C for 3 hours,%	IS 6719	0.5

^{*}Test specimen made after milling the granules and then in compression molded at 140 °C for 10 min with 200kg / cm2 hydraulic pressure

PROCESSING TECHNIQUE:

- 1. The recommended processing temperatures are $140^{0}c$ to $180^{0}c$, However the processing Temperature may be adjusted as per requirement for individual operations.
- 2. The PVC compound KI-55 provides excellent surface finish and outstanding output rates over a broad range of running condition.
- 3. For smooth processing and better results it is recommended to preheat the material before use.

<u>PACKAGING</u>: Pellet form and packed in 25 kg HDPE woven sacks with inner liner to ensuring prevention from uptake of moisture and contamination.

STORAGE:

Material shall be kept in a cool dry place.

NOTE: **We can also offer Tailor Made compounds with specification of your choice.

(The information given in the document is believed to be reliable and is given in good faith but without warranty. The user should test the product to assertion the suitability for intended use. The product specification or the whole document is subject to change without any prior notice.)

FOR MORE INFORMATION PL CONTACT AT:

Head Office:

2B Pretoria Street, Kolkata-71 Tel: 91-33-22823744/45/3671 Fax:91-33-22823739

E-mail: kolkata@kkalpana.co.in Website:www.kkalpanagroup.com