

Kkalpana Industries (India) Limited

GRADE	KALPLENE PP 1T
FEATURE	PP TALC FILLED 10 %
PRESENTATION	PRE COLOURED /NATURAL / BLACK

TECHNICAL DATA SHEET

PROPERTIES	ASTM TEST METHOD	TEST CONDITION	UNIT	KALPLENE PP 1T COLOR XXXX
PHYSICAL PROPERTIES at 23 °C	METHOD			(VALUE)
Melt Flow Rate	D-1238	230°C/2.16kg	gm/10 min	06 ± 01
Specific Gravity*	D-792		-	0.99±0.02
THERMAL PROPERTIES Heat Deflection Temperature* 12.7mm x 6.4mm x 127mm Bar	D-648	18.56 Kg/cm² Annealed at 110 Deg C/2 Hr	°C	90 ± 10
MECHANICAL PROPERTIES Notched Izod Impact Strength	D-256	3.2mm at 23 ⁰ C	Kgfcm/cm	3.5 ± 1
Tensile Strength at yield	D-638	50 mm/min	Kg/cm²	220 ± 20
Flexural Modulus*	D-790	5 mm/min	Kg/cm²	15000 ± 1000

To be measured as & when necessary It is necessary to pre-dry material at 85°C for 2 to 3 hours prior to processing. Inj Mold Condition - 170 -190 °C

DISCLAIMER:

The above Technical Data Sheet presents information and data, true and accurate to the best of our

No warranty express or implied can be made regarding performance or otherwise.

(As this is computer generated, no signature is required)