

## Kkalpana Industries (India) Limited

GRADE	KALPLOY P-P2G COLOR XXXX
FEATURE	PBT/PET 20%GF GEN PURPOSE INJ MOL APPLICATION
PRESENTATION	PRECOLORED (WHITE)

## TYPICAL PROPERTY DATA

PROPERTIES	ASTM TEST METHOD	TEST CONDITION	UNIT	KALPLOY P-P 2G COLOR XXXX ( VALUE)
PHYSICAL PROPERTIES at 23 °C				
Specific Gravity*	D-792		-	1.46±0.02
THERMAL PROPERTIES				
Heat deflection temperature 12.7mm ×6.4mm×127mm bar	D-648	18.56Kg/cm²	°c	200± 2
FLAMMABILITY	UL-94	-	-	НВ
MECHANICAL PROPERTIES				
Notched Izod impact strength	D-256	3.2mm At 23°c	Kgfcm/cm	3.5 ± 1
Tensile Strength at yield	D-638	50 mm/min	Kg/cm²	1100 ± 30

To be measured as & when necessary It is necessary to pre-dry material at 85°C for 2 to 3 hours prior to processing.

## **DISCLAIMER:**

The above Technical Data Sheet presents information and data, true and accurate to the best of our knowledge. No warranty express or implied can be made regarding performance or otherwise.

(As this is computer generated, no signature is required)